

# TRAFFIC PARTS INC.

P.O. BOX 837  
 SPRING, TX 77383-0837

800-345-6329

[SALES@TRAFFICPARTS.COM](mailto:SALES@TRAFFICPARTS.COM)  
[WWW.TRAFFICPARTS.COM](http://WWW.TRAFFICPARTS.COM)

## PANEL MOUNT FLASHERS

SPECIFICATIONS	TP# 1039 (25DF) 2 circuit	TP# 6112 (12DC10DF) 2 circuit
Operating Voltage	60-135 VAC	6-24 VDC
Load Current	25 Amps (w/adequate heat sinking @ 77°F)	10 Amps (w/adequate heat sinking @ 77°F)
Temperature Range	-30° F to 165° F	-30° F to 165° F
Flash Rate (per circuit)	56-1/4 flasher/minute standard (other rates are available upon request)	55 flasher/minute standard
Size	1-3/4" x 2-1/4"	1-3/4" x 2-1/4"
Mounting	Flat surface w/2 mounting holes (top/bottom)	Flat surface w/2 mounting holes (top/bottom)



TP# 6112  
 Pictured



TP# 2935  
 Pictured

## MUSHROOM FLASHERS

SPECIFICATIONS	TP# 2935 2 circuit (yellow)	TP# 5810 2 circuit (green)	TP# 1940 2 circuit (black)
Operating Voltage	95-135 VAC	95-135 VAC	95-135 VAC
Load Current	3 Amps	3 Amps	3 Amps
Temperature Range	-30° F to 165° F	-30° F to 165° F	-30° F to 165° F
Flash Rate	56-1/4 flashes /minute	56-1/4 flashes /minute	56-1/4 flashes /minute
Size	1-7/8" Overall Height	1-7/8" Overall Height	1-7/8" Overall Height
Mounting	Dual purpose mounting in top or bottom of signal and seals off opening	Dual purpose mounting in top or bottom of signal and seals off opening	Dual purpose mounting in top or bottom of signal and seals off opening