

TRAFFIC PARTS INC.

P.O. BOX 837
 SPRING, TX 77383-0837

800-345-6329

SALES@TRAFFICPARTS.COM
WWW.TRAFFICPARTS.COM

PANEL MOUNT FLASHERS

SPECIFICATIONS	TP# 1039 (25DF) 2 circuit	TP# 6112 (12DC10DF) 2 circuit
Operating Voltage	60-135 VAC	6-24 VDC
Load Current	25 Amps (w/adequate heat sinking @ 77°F)	10 Amps (w/adequate heat sinking @ 77°F)
Temperature Range	-30° F to 165° F	-30° F to 165° F
Flash Rate (per circuit)	56-1/4 flasher/minute standard (other rates are available upon request)	55 flasher/minute standard
Size	1-3/4" x 2-1/4"	1-3/4" x 2-1/4"
Mounting	Flat surface w/2 mounting holes (top/bottom)	Flat surface w/2 mounting holes (top/bottom)



TP# 6112
 Pictured



TP# 2935
 Pictured

MUSHROOM FLASHERS

SPECIFICATIONS	TP# 2935 2 circuit (yellow)	TP# 5810 2 circuit (green)	TP# 1940 2 circuit (black)
Operating Voltage	95-135 VAC	95-135 VAC	95-135 VAC
Load Current	3 Amps	3 Amps	3 Amps
Temperature Range	-30° F to 165° F	-30° F to 165° F	-30° F to 165° F
Flash Rate	56-1/4 flashes /minute	56-1/4 flashes /minute	56-1/4 flashes /minute
Size	1-7/8" Overall Height	1-7/8" Overall Height	1-7/8" Overall Height
Mounting	Dual purpose mounting in top or bottom of signal and seals off opening	Dual purpose mounting in top or bottom of signal and seals off opening	Dual purpose mounting in top or bottom of signal and seals off opening